## VERSATEX Canuas Series BEAUTY OF WOOD, DUBABILITY OF PVC.

The VERSATEX Canvas Series has been developed to add contrast to your porch ceilings and interior trim projects. This innovation combines an exterior grade laminate featuring warm woodgrain finishes with long-lasting, maintenance-free VERSATEX profiles. Through the Canvas Series, VERSATEX delivers the look of rich hardwoods without knots and without labor-intensive re-staining requirements.

	>	$\sim$	$\Longrightarrow$
$\sub$	~ <u>`</u>	$\frown$	$\rightarrow$
CANVAS SERIES			
Profile	Actual Width	16'	18'
WP4	3/4" X 5 1/2"		•
Stealth Bead	1/2" X 6"		•
4" Crown	9/16" X 3 5/8"	•	
Bed Mould	9/ <sub>16</sub> " X 3/4"	•	

• All profiles available in all five finishes

Color-matched touch-up kit to be included form distributor

Handling guides available at versatex.com/canvas-series













- \* NOTE: ADHESIVES AND ACETONE CAN DAMAGE THE APPEARANCE OF CANVAS SERIES PRODUCTS! DO NOT USE FOR INSTALLATION.
- All Canvas Series products are to be handled like you would a stained piece of mahogany, walnut or any other premium wood and not like dimensional lumber. Keep the product on a skid and covered until time of installation. The faux stained pieces should never be stored on the ground, on asphalt, or on any rough surface face down. Boards should be removed from skids by lifting at both ends when possible—friction between laminate and bare board may cause minor marking. See cleaning tips for removal method.
- Refer to porch ceiling installation instructions in the VERSATEX Contractor Handbook for recommendations and best practices.

 Use matching end cut coating applicator for cut board edges and wax stick nail hole filler to cover exposed fastener holes.

CLEANING CANVAS SERIES

- Wipe material with gentle cleanser like Simple Green cleaner and a soft cloth.
- If marking occurs from boardto-board friction, WD-40, Pledge, and Armor All can also be used but will require extra wiping to prevent leaving shiny residue.

WARNING: DO NOT use abrasive scrub pads like Scotch Brite pads or any solvent like acetone and toluene! They will break down the laminates and dull the surface.

